

Adcos NV  
Italiëlei 189 bus 2  
B-2000 Antwerpen  
Belgium



Tel +32 (0)3 385 38 50  
Fax +32 (0)3 385 38 52  
info@adcosgroup.com  
www.adcosgroup.com

### DECLARATION OF PERFORMANCE

Nr. 09-300

1. Unique identification code of the product-type	ACRYLINJECT ELASTIC
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	Each delivery of the product is identified by the name of the product and by the batch number
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Products and systems for the protection and repair of concrete structures. Injection products for ductile filling of cracks according to EN 1504-5
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	ADCOS NV Ambachtsstraat 15 2390 Malle Belgium
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard	LGAI Technological Center/Applus - 0370 performed the - Initial inspection of the manufacturing plant and of factory production control; - Continuous surveillance, assessment and evaluation of factory production control; and - Issued a certificate of conformity of the factory production control


8. Declared performance		
Essential characteristic	Performance	Harmonised technical specification
Determination of watertightness of injected cracks without movement in concrete	No water leak	EN 14068
Compatibility with concrete	Weight variation reach a constant a constant level before 28 days 35,6 %	EN 14498
Determination of viscosity	33 mPa.s	EN ISO 3219
Volume and weight changes of injection products after air drying and water storage cycles	Expansion ratio reach a constant level	EN 14498
Workable time	10 °C: 36 23 °C: 23 30 °C: 15	EN ISO 9514

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

date: 15.05.2017

Signed for and on behalf of the manufacturer by:

  
Johan Devroe  
Managing Director